Select if Revised	Asphalt Sealant				<u>Date:</u>	9/30/2025			
Describe revision, if applicable							Year of First Submittal:		
Project Overview:	Cleaning of asphalt, repair of cracks and potholes and commercial-grade asphalt emulsion or coal tar sealer is applied and parking lots are restriped. Ongoing for all GCPS properties in need.								
Requesting Department	Schools			Est. Useful Life 5-10 Years					
Location (address)				Start Year		2027			
Magisterial District	Multiple			Est. Completion Year Beyond 5			ears		
Annual Recurring Cost	click drop-down l	ist		Category		Improvement to Existing Facility			
Number of Residents Served				Primary Board	Priority	Education	2 Zhiotang i domey		
					5-Year CIP				
Expenditure Descrip	tion	Total Project Request	Budget Year	Planning Years				Beyond 5 Years	
			FY2027	FY2028	FY2029	FY2030	FY2031	FYI only	
Land Acquisition		\$ -						•	
A&E		-							
Construction		-							
Equipment		-							
Other		-							
Total Proposed Capital Costs		\$ -	\$ -	\$ -	\$ -	\$ -	\$ -	\$ -	
Source of Funding		Total Funding	FY2027	FY2028	FY2029	FY2030	FY2031	Beyond 5 Years	
Grant		\$ -						•	
Donations		-							
Fund Balance-Committed		-							
County Funds		-							
Total Capital Funding		\$ -	\$ -	\$ -	\$ -	\$ -	\$ -	\$ -	
		9	Describe Funding Sources (If Not County Funds) Describe Annual						
			Recurring Costs						

	Total Droinet	5-Year CIP					
Project Element	Total Project Request	Budget Year	Budget Year Planning Years				
	Request	FY2027	FY2028	FY2029	FY2030	FY2031	FYI only
Asphalt Sealant	\$ -						
	-						
	-						
	-						
	-						
	-						
	-						
	-						
	-						
	-						
	-						
Total Proposed Capital Costs	\$ -	\$ -	\$ -	\$ -	\$ -	\$ -	\$ -

(it necessary)	The asphalt is thoroughly cleaned, any cracks or potholes are repaired, and then a commercial-grade asphalt emulsion or coal tar sealer is applied. At least two coats are applied to create an impermeable, protective layer against water, oil, and UV rays. Once cured, the parking lots are restriped.
Space below is available for any add	itional details not provided above:
Sealing is recommended every three	to five years.
Project Alternative:	